

ANTARES BLACK-OUT-COLOUR 1003

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	2300	R	T	A	R	T	A			
2303	ecru	%o	%o	%o	47%	0%	53%	44%	0%	56%	6-7	0,34	0,46
2302	mocha	%o	%o	%o	38%	0%	62%	33%	0%	67%	6-7	0,34	0,46
9139	flint	%o	%o	%o	31%	0%	69%	28%	0%	72%	6-7	0,34	0,46
5173	royal	%o	%o	%o	28%	0%	72%	24%	0%	76%	6-7	0,34	0,46
6115	yellow	%o	%o	%o	35%	0%	65%	30%	0%	70%	6-7	0,34	0,46
8162	red	%o	%o	%o	30%	0%	70%	26%	0%	74%	6-7	0,34	0,46

Usable for
Colour Range
Composition
Width
Cutting Process
Processing Direction

Roller / Vertical / Panel Track
6 (coloured back side)
100 % PES
89 / 127 / 2300 mm
cold
warp & weft

Weight
Thickness
Moisture proofed
PVC free
OekoTex

420 g/m²
0,50 mm
yes
yes
yes




Flame
retardant

DIN 4102, B1
NF P 92-503-507, M1
BS 5867 part 2
UNI 8456-UNI 9174
C1 / EN 13772 class 1
NFPA 702- USA



suitable for
workstations



D
black-out



Standard 100
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.